صنايع نسوز پرتو دادمهر خراسان



Brand Name:

DMLWC 22

Type of Product: Light Weight Castable

Chemical Analysis (%)

| Al ₂ O ₃ | SiO ₂ | CaO | Fe ₂ O ₃ | TiO ₂ |
|--------------------------------|------------------|-------|--------------------------------|------------------|
| 33-37 | 38-42 | 12-14 | 5-8 | 2-3 |

Physical Properties

| Raw Material Basis | Chamotte |
|---|----------|
| Max Service Temperature(°C) | 1210 |
| Bulk Density after drying at 110°C (Kg/m ³) | <1100 |
| Approximate amount of water required (%) | 44-55 |
| Grain Size (mm) | 0 -4 |

Thermo mechanical Properties

| Properties After drying | at 110°C | at 1200°C |
|---|----------|------------|
| Cold Crushing Strength (Kg/ Cm ²) | >20 | >30 |
| Modulus of Rupture (Kg/ Cm ²) | 10-25 | 5-10 |
| Linear Change (%) | | -1 to +0.1 |

Packing in 25 kg Bags

All date subject to reasonable deviations, and therefore, should not be used for specification purposes.

ASTM Test Methods, where applicable, used determination of data.

Address: 304 No, 48 Seyedrazi, Mashhad, Iran Factory: Industrial City, Kalat Road, Mashhad www.partodadmehr.com Tel: 051-360 343 66 Telfax: 051-360 340 99