صنايع نسوز پرتو دادمهر خراسان



# **Brand Name:**

**DMLWC 23** 

Type of Product: Light Weight Castable

## **Chemical Analysis (%)**

Al <sub>2</sub> O <sub>3</sub>	SiO <sub>2</sub>	CaO	Fe <sub>2</sub> O <sub>3</sub>	TiO <sub>2</sub>
35-40	35-40	9-13	5-7	2.5-3.5

### **Physical Properties**

Raw Material Basis	Chamotte
Max Service Temperature(°C)	1260
Bulk Density after drying at 110°C (Kg/m <sup>3</sup> )	<1500
Approximate amount of water required (%)	31-36
Grain Size (mm)	0 -5

## **Thermo mechanical Properties**

Properties After drying	at 110°C	at 1200°C
Cold Crushing Strength (Kg/ Cm <sup>2</sup> )	>30	>30
Modulus of Rupture (Kg/ Cm <sup>2</sup> )	10-35	9-15
Linear Change (%)		-1.8 to -1.2

## Packing in 20 kg Bags

All date subject to reasonable deviations, and therefore, should not be used for specification purposes.

ASTM Test Methods, where applicable, used determination of data.

Address: 304 No, 48 Seyedrazi, Mashhad, Iran Factory: Industrial City, Kalat Road, Mashhad www.partodadmehr.com Tel: 051-360 343 66 Telfax: 051-360 340 99